




Model: BT-1510-N { & BT-1510-NB }

Description:	Bias Tee
Operating Frequency:	10 KHz – 1.5 GHz
Insertion Loss:	1.1 dB Max
Isolation DC to RF:	10-20 KHz 20 dB Min
	20-40 KHz 30 dB Min
	40 KHz – 1.5 GHz 40 dB Min
VSWR:	1.35:1 Max ; [1.8:1 over 10-20 KHz]
Bias Voltage:	100 Volts Max
Bias Current:	500 mA Max
Bias Frequency Bandwidth:	DC-1 KHz
RF Power Handling:	20W CW/AVG
Bias DC Resistance:	3 Ω Max
RF Connector:	N (F)
RF+DC Connector:	N (F)
Bias Connector:	Standard Solder-Pin
	{Add suffix "B" for Bias Connector with BNC(F) <> Model: BT-1510-NB }
Impedance:	50 Ω Nominal
Quality:	Best-Commercial-Grade

Environmental Ratings:

Temperature:	{Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Model: BT-1510-N ; { DC-Port with Solder Pin }



Model: BT-1510-NB ; { Option "B"; DC-Port with BNC(f) }

