



Model: DC-CH00-10S


Description:.....	Directional Coupler
Operating Frequency:.....	0.9 – 2.1 GHz
Coupling (reference to input):.....	10 ± 0.75 dB Nominal
Coupling Flatness (Sensitivity):.....	± 0.3 dB Max
Insertion Loss (including coupled power):.....	0.7 dB Max
Directivity:	25 dB Min
VSWR:	Line..... 1.15:1 Max
.....	Couple..... 1.15:1 Max
Power Handling:	10W Cw/Avg, 1KW Peak
Connectors:	SMA (f)
Impedance:.....	50 Ohms Nominal
Quality:.....	Best-Commercial-Grade

Environmental Ratings:

Temperature:.....	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:.....	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:.....	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:.....	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:.....	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:.....	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline

("A" = 3.200" [81.3mm])



Weight
1.8 oz [51.0 g]