




Model: DC-G000-30S

Description:	Directional Coupler
Operating Frequency:	12.4 - 18 GHz
Coupling (reference to input):	30 ± 1 dB Nominal
Coupling Flatness:	± 0.7 dB Max
Total Insertion Loss (including coupled power):	0.60 dB Max
Directivity:	12 dB Min
VSWR: Line	1.40:1 Max
Couple	1.55:1 Max
Power Handling:	50W Cw/Avg, 1KW Peak
Connectors:	SMA (f)
Impedance:	50 Ohms Nominal
Quality:	Best-Commercial-Grade

Environmental Ratings:

Temperature:	{Operating: -40°C to +85°C} & {Storage: -50°C to +100°C}
Humidity:	MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:	MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:	MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude:	MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:	MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Outline
 ("A" = 1.250" [31.8 mm])



Weight
0.75 oz [21.3g]