



Model: SR-U04W-10S

Description: SP10T, Reflective, PIN-Switch

Operating Frequency:..... 0.5 – 18 GHz

Insertion Loss:..... 4.4 dB Max

Isolation (Arm-to-Arm):

0.5 – 8 GHz	8 – 18 GHz
80 dB Min	70 dB Min

VSWR ("ON" RF Paths): 2:1 Max

Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 350 ns Max

On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 400 ns Max

Operating Power: CW&AVG +27dBm Max

..... Peak:..... 5W @ 1μS PW & 10% Duty-Cycle Max

Control Input Characteristics: Std. TTL / Unit-Load / Floating-High

Control Logic: 10-Controls, Logic "0" = RF Path "ON"

Power Supplies: +5(±0.25)V @ 120mA Max

..... -12(±0.5)V @ 110mA Max

Connectors (RF):..... SMA (f), Removable

Connectors (Supplies/Controls) Solder Pins

Impedance: 50 Ω Nominal

Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}

Humidity:..... MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)

Shock:..... MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)

Vibration:..... MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)

Altitude:..... MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)

Temp. Shock:..... MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

A1 [+5(±0.25)V / -5(±0.25)V] *

A2 [+5(±0.25)V / -15(±0.5)V]

A3 [+12(±0.5)V / -12(±0.5)V]

A4 [+15(±0.5)V / -15(±0.5)V]

■ **RF Connectors**

B1 [J1 – J10 Ports with SMA(M)]

B2 [All SMA (M)]

B3 [COM Port with SMA(M)]

■ **Control/Supply Connector(s)**

E1 [15-Pin Micro-D Male (Plug) with Jack-Posts]

.... see Fig.2 in Web Site for Outline Drawing

■ **Control Function**

F1 [Inverse Logic, ("1" = Path "ON")]

F2 [4-Bit Binary Controls + Enable] ; see below for
"Outline Drawing" and "Function Table"

■ **Video Suppression Filter**

G1 [VF @ COM Port <> 0.25 dB additional Loss]

G2 [VF @ J1 – J10 Ports <> 0.25 dB additional Loss]


G3 [VF @ All Ports <> 0.5 dB additional Loss]

* Recommended for Low Power Consumption <> Additional Switching Delay (ON/OFF time)



Model: SR-U04W-10S

Outline




Weight	Tolerances
3.8 oz [108g]	±0.015" [±0.38mm]



Model: SR-U04W-10S

Outline (Option "F2" for 4-Bit Binary Control + Enable)



Weight	Tolerances
3.8 oz [108g]	±0.015" [±0.38mm]



Model: SR-U04W-10S

Function Table for Option "F2" (4-Bit Binary Control + Enable)

INPUTS					RF PATH FROM "COM" PORT TO "JXX" PORT									
E	B3	B2	B1	B0	J1	J2	J3	J4	J5	J6	J7	J8	J9	J10
0	0	0	0	0	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
0	0	0	0	1	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
0	0	0	1	0	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF
0	0	0	1	1	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF
0	0	1	0	0	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF
0	0	1	0	1	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF
0	0	1	1	0	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF
0	0	1	1	1	OFF	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF
0	1	0	0	0	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF
0	1	0	0	1	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	ON
1	X	X	X	X	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF