



Model: SW-L440-2S

Description: SP2T, Reflective, PIN-Switch
Operating Frequency: 2 - 14 GHz
Insertion Loss: 2.2 dB Max
Isolation (Arm-to-Arm):

Table with 2 columns: 2 - 12.4 GHz, 12.4 - 14 GHz. Row 1: 55 dB Min, 50 dB Min.

VSWR (RF Path "ON" or "OFF"): 1.5:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): 20 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 50 ns Max
Phase Balance (Deviation from Median): ±5° max
Operating Power: CW&AVG: +27dBm Max, Peak: 5W @ 1µS PW & 10% Duty-Cycle Max
Control Input Characteristics: Std. TTL / Unit-Load / Floating-High
Control Logic: 2-Controls, Logic "0" = RF Path "ON"
Power Supplies: +5(±0.25)V @ 50mA Max, -12(±0.5)V @ 50mA Max
Connectors (RF): SMA (f), Removable
Connectors (Supplies/Control): Solder Pins
Impedance: 50 Ω Nominal
Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

Supply Voltages

- A1 [+5(±0.25)V / -5(±0.25)V]
A2 [+5(±0.25)V / -15(±0.5)V]
A3 [+12(±0.5)V / -12(±0.5)V]
A4 [+15(±0.5)V / -15(±0.5)V]

RF Connectors

- B1 [J1 & J2 Ports with SMA(M)]
B2 [All SMA (M)]
B3 [COM Port with SMA(M)]

Control Connectors

- C1 [SMC(Jack), 50 Ω]
C2 [SMB(Jack), 50 Ω]

Control Impedance

- D1 [50 Ω, Internally Terminated]

Control Function

- F1 [Inverse Logic, ("1" = Path "ON")]
F2 [Single Toggle Control ("1" for J1 path "ON")]


Video Suppression Filter

- G1 [VF @ COM Port <> 0.25 dB additional Loss]
G2 [VF @ J1 & J2 Ports <> 0.25 dB additional Loss]
G3 [VF @ All Ports <> 0.5 dB additional Loss]



Model: SW-L440-2S

Outline



| Weight | Tolerances |
|-----------------|-------------------|
| 0.7 oz [19.8 g] | ±0.015" [±0.38mm] |