



Model: SW-V200-2S

Description: SP2T, Reflective, PIN-Switch
Operating Frequency: 0.1 - 18 GHz
Insertion Loss: 2.2 dB Max
Isolation:

0.1 – 10 GHz	10 - 18 GHz
65 dB Min	55 dB Min

VSWR (Path "ON"): 1.6:1 Max
Rise/Fall Time (10% to 90% RF, 90% to 10% RF): 70 ns Max
On/Off Time (50% TTL to 90% RF, 50%TTL to 10% RF): 170 ns Max
Phase Balance (Deviation from Median): $\pm 3^\circ$ max
Operating Power: CW / AVG +30 dBm Max *
..... * {+27dbm Max below 300MHz}
..... Peak: 5W @ 1 μ S PW Max
Control Input Characteristics: TTL /Unit-Load, Floating-High
Control Logic: 2-Controls, Logic "0" = RF Path "ON"
Power Supplies: +5(± 0.25) V @ 70mA Max
..... -12(± 0.5) V @ 50mA Max
Connectors (RF): SMA (f), Removable
Connectors (Supplies/Controls) Solder Pins
Impedance: 50 Ω Nominal
Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ Supply Voltages

- A1 [+5(± 0.25)V / -5(± 0.25)V] *
- A2 [+5(± 0.25)V / -15(± 0.5)V]
- A3 [+12(± 0.5)V / -12(± 0.5)V]
- A4 [+15(± 0.5)V / -15(± 0.5)V]

■ RF Connectors

- B1 [J1 & J2 Ports with SMA(M)]
- B2 [All SMA (M)]
- B3 [COM Port with SMA(M)]

■ Control Connectors

- C1 [SMC(Jack), 50 Ω]
- C2 [SMB(Jack), 50 Ω]

■ Control Impedance

- D1 [50 Ω , Internally Terminated]

■ Control Function


- F1 [Inverse Logic, ("1" = Path "ON")]
- F2 [Single Toggle Control ("1" for J1 path "ON")]

* Recommended for Low Power Consumption <> Additional Switching Delay (On/Off Time)



Model: SW-V200-2S

Outline



Weight	Tolerances
0.7 oz [19.8 g]	±0.015" [±0.38mm]