



Model: SR-P010-4S

Description: SP4T, Absorptive, PIN-Switch
Operating Frequency: 2 - 20 GHz
Insertion Loss: 3.2 dB Max
Isolation:

Table with 2 columns: Frequency Range (2-14 GHz, 14-20 GHz) and Isolation (70 dB Min, 60 dB Min)

VSWR (RF Path "ON" or "OFF"): 1.9:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): 40 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 80 ns Max
Operating Power: CW & AVG: +27dBm Max \*
Control Input Characteristics: Std. TTL / Unit-Load / Floating-High
Control Logic: 4-Controls, Logic "0" = RF Path "ON"
Power Supplies: +5(+0.25)V @ 140mA Max
Connectors (RF): SMA (f), Removable
Connectors (Supplies/Controls): Solder Pins
Impedance: 50 Ohms Nominal
Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06" double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

Supply Voltages

- A1 [+5(+0.25)V / -5(+0.25)V] \*
A2 [+5(+0.25)V / -15(+0.5)V]
A3 [+12(+0.5)V / -12(+0.5)V]
A4 [+15(+0.5)V / -15(+0.5)V]

RF Connectors

- B1 [J1 - J4 Ports with SMA(M)]
B2 [All SMA (M)]
B3 [COM Port with SMA(M)]

Control Function

- F1 [Inverse Logic, ("1" = Path "ON")]
F2 [2-Bit Binary Controls + Enable]; see below for "Outline Drawing" and "Function Table"

Video Suppression Filter


- G1 [VF @ COM Port <> 0.25 dB additional Loss]
G2 [VF @ J1 - J4 Ports <> 0.25 dB additional Loss]
G3 [VF @ All Ports <> 0.5 dB additional Loss]

\* Recommended for Low Power Consumption <> Additional Switching Delay (ON/OFF time)



Model: SR-P010-4S

**Outline**




Weight	Tolerances
1.3 oz [36.9g]	±0.015" [±0.38mm]



Model: SR-P010-4S

**Outline Drawing (SP4T with Option "F2")**



**Function Table for Option "F2" (2-Bit Binary Control + Enable)**

INPUTS			RF PATH			
E	B1	B0	J1	J2	J3	J4
1	0	0	ON	OFF	OFF	OFF
1	0	1	OFF	ON	OFF	OFF
1	1	0	OFF	OFF	ON	OFF
1	1	1	OFF	OFF	OFF	ON
0	X	X	OFF	OFF	OFF	OFF