



**Model: SW-J010-5S**

Description:..... SP5T, Absorptive, PIN-Switch

Operating Frequency:..... 0.5 – 12.4 GHz

Insertion Loss:

0.5 – 6 GHz	6 – 12.4 GHz
2.4 dB Max	2.7 dB Max

Isolation:

0.5 – 6 GHz	6 –12.4 GHz
65 dB Min	55 dB Min

VSWR (RF Path “ON” or “OFF”): ..... 1.7:1 Max  
 Rise/Fall time (10% to 90% RF, 90% to 10% RF): ..... 35 ns Max  
 On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): ..... 60 ns Max  
 Phase Error (Port-to-Port): ..... ±5° max  
 Operating Power:..... CW&AVG..... +24dBm (+27dbm @ COM Port)  
 ..... Peak: ..... 8W @ 1µS PW Max  
 Harmonic Distortion: ..... 65dBc Max @ +27dBm  
 Control Input Characteristics: ..... TTL /Unit-Load, 5-Controls / Flouting-High  
 Control Logic:..... Logic “0” = RF Path “ON”  
 Power Supplies:..... +5(±0.25)V @ 160mA Max  
 ..... -12(±0.5)V @ 80mA Max  
 Connectors (RF):..... SMA (f), Removable  
 Connectors (Supplies/Controls) ..... Solder Pins  
 Impedance:..... 50 Ohms Nominal  
 Weight:..... 1.3 oz [36.9 g]  
 Quality:..... Best-Commercial-Grade

**Environmental Ratings:**

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}  
 Humidity: ..... MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)  
 Shock: ..... MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)  
 Vibration: ..... MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)  
 Altitude: ..... MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)  
 Temp. Shock: ..... MIL-STD-202F, Method 107D, Cond. A (5 cycles)

**Available Options:**

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

- A1 [ +5(±0.25)V / -5(±0.25)V ]
- A2 [ +5(±0.25)V / -15(±0.5)V ]
- A3 [ +12(±0.5)V / -12(±0.5)V ]
- A4 [ +15(±0.5)V / -15(±0.5)V ]

■ **RF Connectors**

- B1 [ J1 – J5 Ports with SMA(M) ]
- B2 [ All SMA (M) ]
- B3 [ COM Port with SMA(M) ]

■ **Control Function**

- F1 [ Inverse Logic, (“1” = Path “ON”) ]

■ **Video Suppression Filter**

- G1 [ VF @ COM Port <> 0.25 dB additional Loss ]
- G2 [ VF @ J1 – J5 Ports <> 0.25 dB additional Loss ]
- G3 [ VF @ All Ports <> 0.5 dB additional Loss ]



Model: SW-J010-5S

### Outline

