



Model: SR-S510-6S

Description: SP6T, Absorptive, PIN-Switch
Operating Frequency:..... 2 – 18 GHz
Insertion Loss:..... 3.6 dB Max
Isolation (Arm-to-Arm):

2 – 9 GHz	9 –18 GHz
70 dB Min	60 dB Min

VSWR (“ON” Paths & “OFF” Ports):..... 1.9:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 15 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF): 40 ns Max
Operating Power: CW & AVG +27dBm Max *
..... * (+24dBm Max into “JX” Port @ Off-State)
..... Peak:..... 5W @ 1 μ S PW & 10% Duty-Cycle Max
Control Input Characteristics:..... Std. TTL / Unit-Load / Floating-High
Control Logic: 6-Controls, Logic “0” = RF Path “ON”
Power Supplies: +5($\pm$ 0.25)V @ 170mA Max
..... -12($\pm$ 0.5)V @ 70mA Max
Connectors (RF):..... SMA (f), Removable
Connectors (Supplies/Controls) Solder Pins
Impedance: 50 Ω Nominal
Quality: Best-Commercial-Grade

Environmental Ratings:

Temperature: {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity:..... MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock:..... MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration:..... MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)
Altitude:..... MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock:..... MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

A2 [+5($\pm$ 0.25)V / -15($\pm$ 0.5)V]
A3 [+12($\pm$ 0.5)V / -12($\pm$ 0.5)V]
A4 [+15($\pm$ 0.5)V / -15($\pm$ 0.5)V]

■ **Control Function**

F1 [Inverse Logic, (“1” = Path “ON”)]
F2 [3-Bit Binary Controls + Enable] ; see below for
“Outline Drawing” and “Function Table”

■ **RF Connectors**

B1 [J1 – J6 Ports with SMA(M)]
B2 [All SMA (M)]
B3 [COM Port with SMA(M)]


■ **Video Suppression Filter**

G1 [VF @ COM Port <> 0.25 dB additional Loss]
G2 [VF @ J1 – J6 Ports <> 0.25 dB additional Loss]
G3 [VF @ All Ports <> 0.5 dB additional Loss]



Model: SR-S510-6S


Outline



Weight	Tolerances
2.1 oz [59.5g]	±0.015" [±0.38mm]



Outline Drawing (SP6T with Option “F2”)



INPUTS				RF PATH					
E	B2	B1	B0	J1	J2	J3	J4	J5	J6
0	0	0	0	ON	OFF	OFF	OFF	OFF	OFF
0	0	0	1	OFF	ON	OFF	OFF	OFF	OFF
0	0	1	0	OFF	OFF	ON	OFF	OFF	OFF
0	0	1	1	OFF	OFF	OFF	ON	OFF	OFF
0	1	0	0	OFF	OFF	OFF	OFF	ON	OFF
0	1	0	1	OFF	OFF	OFF	OFF	OFF	ON
1	X	X	X	OFF	OFF	OFF	OFF	OFF	OFF